	**Key features** Up to 32-ch IP camera inputs H.265+/H.265/H.264+/H.264 Up to 1-ch@12 MP or 1-ch@8 MP or 3-ch@4 MP decoding capacity 4K (3840 × 2160) HDMI Video Output 4 x SATA HDD Interfaces(up to 8TB capacity per HDD) Up to 160 Mbps incoming bandwidth

Model Number		**N84PBH**
NVR		
Video & Audio	Decoding Format	H.265+/H.265/H.264+/H.264
	IP Video Input	32 Channel, up to 12MP resolution
	Video Output	HDMI up to 4K, VGA up to 1080p
	Video output mode	HDMI/VGA simultaneous output
	Audio Input/Output	1/1 RCA
	Incoming/outgoing Bandwidth	160/80 Mbps
	Max Recording Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	Max Playback Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	Max Playback Channel	16CH
	Decoding Capability	1-ch@12 MP/1-ch@8 MP/3-ch@4 MP/6-ch@1080p The length or width of camera resolution (each track) cannot exceed 4096 pixels.
	Network protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
	Remote Connection	64
Hard Drive	HDD	4 SATA Interface
	HDD Capacity	Up to 8 TB Capacity for Each HDD(32 TB total)
External Interface	Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
	Alarm Input/Output	16/4
	Serial Interface	1 RS-485 (Half-Duplex), 1 RS-232
	USB	Front Panel: 2X USB 2.0; Rear Panel: 1X USB 2.0
General	Operating Power	100-240V AC
	Power Consumption	≤ 15 W(without HDD and PoE off)
	Working Temperature	14 °F — 131 °F/-10 °C — +55 °C
	Dimensions (W X H X D)	440 × 397 × 75 mm (17.3"× 15.6" × 3.0")
	Weight (Without Hard Disk)	≤11 lbs. (5 kg)

Packaging Contents	
NVR	1
USB Mouse	1
Power Cable	1
HDD Date Cable	4
HDD Power Cable	1
Screw bag	1
1 m Network cable	1
1.8 m HDMI cable	1
User Manual For NVR	1